



**NUMBER:** 26-001-07

**GROUP:** Revisions

**DATE:** January 12, 2007

*This bulletin is supplied as technical information only and is not an authorization for repair. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without written permission of DaimlerChrysler Corporation.*

**SUBJECT:**

Owner Manual Addendum - Engine Oil Viscosity (SAE Grade) and Capacities - Gasoline Engines - Export Models Only

**MODELS:**

2007	(PM)	Caliber (International Markets)
2007	(MK49)	Compass (International Markets)

**DISCUSSION:**

An Owner's Manual Addendum about Engine Oil Viscosity (SAE Grade) and Capacities - Gasoline Engines In Section 7 Is Available For 2007 PM/MK Vehicles. This addendum can be currently found and printed from Dealerconnect /Techconnect, Or the ITIL/ISIS DVD Dated March, 2007 or later. Locate the SB by document number 26-001-07.

All unsold vehicles in dealer/distributor inventory should have the addendum placed in the Owner Manual.

**POLICY:**

Information Only.



**Stick with the Specialists™**

**OWNER'S MANUAL ADDENDUM**

**THIS ADDENDUM UPDATES INFORMATION ABOUT MAINTENANCE PROCEDURES,  
FLUIDS AND CAPACITIES AND FLUIDS, LUBRICANTS AND GENUINE PARTS  
IN SECTION 7 OF YOUR OWNER'S MANUAL**

**MAINTENANCE PROCEDURES**

**Engine Oil Viscosity (SAE Grade) – Gasoline Engines**

Your vehicle comes equipped from the factory with SAE 5W-20 engine oil as indicated on the engine oil fill cap. The manufacturer recommends using SAE 5W-30 engine oil for all future engine oil change maintenance intervals.

**Engine Oil Selection – Gasoline Engines**

For best performance and maximum protection under all types of operating conditions, use MB 229.31/MB229.51 approved oils. Use Mopar or an equivalent oil approved to MB 229.31/MB229.51.

**FLUIDS AND CAPACITIES**

<b>Engine Oil - With Filter</b>		
All Gasoline Engines Use MB229.31/MB229.51; SAE 5W-30	4.5 Quarts	4.26 Liters

**FLUIDS, LUBRICANTS AND GENUINE PARTS**

Component	Fluids, Lubricants and Genuine Parts
Engine Oil - Gasoline	For best performance and maximum protection under all types of operating conditions, use SAE 5W-30 engine oils that meet the requirements of MB 229.31/MB229.51. Use Mopar or an equivalent oil approved to MB 229.31/MB229.51.

				81-426-07216E
	81-426-07213E	81-426-07223E	81-426-07278B	81-426-07217E
	81-426-07222D	81-426-07231B	81-426-07285B	81-426-07218E
	81-426-07230B	81-426-07232B	81-426-07226D	81-426-07219E
	81-426-07234B	81-426-07229B	81-426-07214E	81-426-07220E
DaimlerChrysler Corporation	81-426-07238B	81-426-07233B	81-426-07215E	81-426-07291A